



REF	DESIGNATION
16-29	LAKCHO constant water level - Polyethylene bowl 50 W
16-31	80 W (for the northern countries)
16-35	STALCHO Stainless steel paddle - Polyethylene bowl 50 W
16-34	80 W (for the northern countries)
16-30	CALDOLAC 5 constant water level - Polyethylene bowl - Heated water 180 W with internal thermostat included
A-532	REMOTE THERMOSTAT FOR FROST-FREE ELECTRIC DRINKING TROUGHS Automatic on/off according to the temperature (3°C / 37.4°F) Watertight cabinet. Max capacity: 1200 W (max 3 transfo. of 400 VA or 6 of 200 VA or 12 of 100 VA).

Foam-insulated HDPE stands

Now with hole for drain hose (plug included):

REF	DESIGNATION
A-574	Height 1000 mm, to be embedded in 400 mm concrete.
A-573	Height 740 mm, to be fixed to the floor ; Especially designed for horses.
A-572	Height 600 mm, to be fixed to the floor
A-570	Height 400 mm, to be fixed to the floor ; Especially designed for little animals: calves, sheeps, goats, ponies



Better than concrete, the LA BUVETTE®'s stands are sturdy and easy to install. The double polyethylene wall is filled with insulating polyurethane foam

Transformers required

230V/24V, shell-type. European norm EN 60.742

REF	DESIGNATION
A-505	50 VA for 1 LAKCHO 50 W or of equal value
A-504	100 VA for 2 LAKCHO 50 W or 1 ISOBAC 100 W or equal to 100 W
A-503	200 VA for 4 LAKCHO 50 W or 2 ISOBAC 100 W or equal to 200 W
A-501	300 VA for 6 LAKCHO 50 W or 3 ISOBAC 100 W or equal to 300 W
A-502	400 VA for 8 LAKCHO 50 W or 4 ISOBAC 100 W or equal to 400 W



OUR ADVICE

Use an electric cable with a suitable diameter for the installation's output.
Consult the chart on the right side.

LAKCHO

Ref. 16-29

Frost-free drinking trough to be mounted on polyethylene or concrete stand (in Ø 300 mm - 11,8").
Large polyethylene bowl with constant level.
Also available in 80 W.



24 V - 50 W
Transformer delivered separately.



STALCHO: with stainless steel paddle.

CALDOLAC 5

Ref. 16-30

24 V - 180 W
Transformer delivered separately. Internal thermostat.



Same as LAKCHO but with more heating capacity and internal thermostat.
It supplies tepid water (auto-regulate temperature).
Ideal for 25 goats or sheeps.

HDPE Stands

Foam-insulated PE Stand with a hole for drain hose. (Plug included).

H 400 mm :
For calves, sheeps,
goats, ponies...

H 600 mm :
Ideal for cattle in the
existing buildings.

H 740 mm :
especially designed
for horses.

H 1000 mm :
Perfect for first
installation.



Accessories

Remote thermostat set on 3°C (37,4°F) for automatic on/off switching with outside sensor: Ref. A-532.



Transformers - 230/24 V obligatory, delivered separately, to be selected depending of the number of drinking troughs.



CHART: CROSS-SECTION OF ELECTRIC CABLE

